TOWN OF CHATHAM HIGHWAY DEPARTMENT

865 Cty Rte 13, Old Chatham, NY 12136 Telephone (518) 794-7281 Fax (518) 794-7281

Application for "DRIVEWAY WORK PERMIT" PERMIT #: D2013-____

	perform work within three (3) months from the date of issuance. Application Fee of <u>\$50.00</u> must be submitted with application that has been applicated to the submitted with application that ham?
Check # Date:	Accepted by:
PROPERTY OWNER:	
MAILING ADDRESS:	
TELEPHONE #:	FAX:
CONTRACTOR:	
ADDRESS:	
TELEPHONE #:	FAX:
(Driveway must be marked out at the proposed inte	TAX GRID#:ersection with the roadway prior to preliminary viewing.)
Industrial / Nature of Business: Residential	
\$ as security that the Town Highway desexpense of the applicant as soon as the work authorized hauthorized to expend all or so much of said deposit as may refuse to do the same. Check # Date:	atham Highway Department, a certified check in the sum of scribed herein will be restored to its original condition at the serein has been completed; and, the Town of Chatham is hereby be necessary for that purpose, should the applicant neglect of the completed by:
ADDITIONAL SPECIAL CONDITIONS:	
Signature of Property Owner	 Date
TOWN USE ONLY:	
Date Received:	Date Inspected:
Date Permit Issued:	Acceptable Not Acceptable
X	X
Signature Highway Superintendent Date	Signature Highway Superintendent Date

CONDITIONS AND RESTRICTIONS

- 1. All work performed under this permit shall be constructed in accordance with the Town of Chatham Highway Specifications.
- 2. The work authorized by this permit shall be performed under the supervision and to the satisfaction of the Town Superintendent of Highways.
- 3. The applicant agrees to pay all necessary expenses incident to the supervision and inspection of the above work by the Town Superintendent of Highways.
- 4. The Town Superintendent of Highways shall be given one week's notice by the applicant of the date when it intends to begin the work authorized by this permit, together with prompt notice of completion of said work.
- 5. The applicant hereby indemnifies and agrees to hold the Town of Chatham harmless from any damages of any kind or nature which may arise during the progress of the work authorized by this permit.
- 6. The applicant certifies to the Town of Chatham that all persons engaged or performing the work authorized hereunder are duly covered by workmen's compensation insurance and that the Town of Chatham shall be held harmless on account thereof.
- 7. Traffic shall be maintained by the applicant on the Town Highway while the work authorized herein is in progress and until its final completion.
- 8. All excavated material will be removed from the site and replaced with processed gravel. Back fill will be tamped in six (6) inch lifts.
- 9. Any required culverts will be of minimum fifteen (15) inch unless otherwise permitted by the Town Highway Superintendent.
- 10. No excavation will be left open overnight. Any opening off a Town Road will be properly barricaded and marked.
- 11. The Town Superintendent of Highways reserves the right at any time to revoke, modify or annul this permit if the applicant fails to comply with the terms and conditions set forth herein.
- 12. Unless otherwise noted, all residential driveways shall be constructed with a blacktop apron constructed over a twelve (12) inch gravel subgrade. In no case shall the apron extend less than 20 feet from the edge of the paved road surface. In no case shall the apron be less than 15 feet wide. The apron shall be constructed of hot mix asphalt concrete plant mix and shall have a finished compacted thickness of three (3) inches.
- 13. The applicant will submit securities in the amount specified by the Highway Department to guarantee the restoration of the site to its original condition. Costs incurred by the Highway Department for corrective measures to the Town highway that may be needed due to conditions related to incomplete or unacceptable permit work shall be borne by the applicant undertaking the activity.
- 14. Culvert length to be determined by Highway Superintendent. Flared head wall ends as required.

DRIVEWAYS

A. PERMITS:

- The owner of the parcel, logger, contractor or the developer shall obtain all necessary permits and construct all driveway entrances to the satisfaction of the governing agency.
- 2. No work shall take place along a Town Highway until a permit has been obtained from the Town Highway Department or governing agency.

B. DESIGN:

- 1. Driveways shall be designed similar to a road intersection. A driveway center line shall be offset from a road intersection center line a minimum of 125 feet. Driveways shall have adequate sight distance.
- 2. Unless otherwise allowed by the Planning Board a separate driveway shall be required for each lot.
- 3. The minimum pavement or gravel width for driveways at the roadway shall be twelve (12') feet. The minimum overhead clearance shall be twelve (12') feet.
- 4. Driveway grades shall have a negative gradient of 2% within (25') feet of the roadway. Where positive elevations are sought, the developer shall submit driveway profiles, grading plan and cross sections to permit a technical evaluation of the proposal by the Highway Superintendent or the Town Engineer.
- 5. The driveway entrance, curbing, gutter, drainage ditch and roadway interference shall be designed:
 - a. Not to channel drainage water from driveway onto or across the roadway.
 - b. Not to channel drainage water from roadway onto driveway.
 - c. Not to interfere with drainage flow along curbing gutter or drainage ditch.
- 6. All positive grade driveways shall continue at positive grade to the edge of pavement of the road to prevent ponding.
- 7. Driveways shall be designed to provide Fire Department apparatus access to within a distance of (150') feet or less of the structure it may be called upon to protect. No turn shall be of such a degree as to prevent access of Fire Department apparatus.
- 8. Driveways shall be able to support a thirty-ton, three axle apparatus.

C. CONSTRUCTION:

- 1. For driveways constructed in wet areas, all unsuitable material shall be excavated and replaced with suitable material. Curtain drains should be installed which discharge into the roadway storm drain system.
- 2. Temporary driveways associated with construction, logging, or other similar use shall be provided with an anti-tracking construction entrance consisting of (12") inch thickness of compacted 1 ½" stone.
- 3. See also Subdivision of Land Regulations.